



Shaping the future.

Brage Statfjord Revitalization

Subsurface Workflow during an Infill Well Project

Vincent Brotte, Force Seminar 11.05.17

- Introduction to Brage Statfjord

- Basis for new wells
- Static model

- Case Study: uncertainty handling during the lifetime of the project
 - Identify phase
 - Select phase

- Conclusion

Introduction to Brage Statfjord

- On production since September 1993, Statfjord has contributed over 50% of the total Brage production (3 other reservoirs)
- Concept: **Sand-Box** → connected reservoir


Sand

*Depositional environment: braided river system
Facies: Amalgamated sand channels, eroded overbank shales, local calcites
Good properties: Darcy sands, Phi ~ 0.25*

Box


*Bounded horst ~ 8x1 km² with 2 segments in communication
2 smaller downthrown blocks in South
Thickness: 75-110 m*

- Dead oil with common initial FWL and limited bottom aquifer: 60m oil column in South, less in North
- STOIP ~ 53 MSm³ / RF >=55%
- 13 historical producers: mostly long horizontal, near reservoir top (now 5 active in South)
- 2 main historical injectors: slanted perforated around and below the initial FWL (now 1 active in South)



Basis for a Well Project in South

- Natural production decline: need for infill targets
- Based on STOIP estimates and historical production:
 - RF: 65% N vs 55% S → Potential in South
 - Backed-up by 4D seismic signal
- Explanations:
 - ratio of (injected water) / (pore volume)
 - well density
- Contingency for South injector failure



4D map: change in AI

observations / starting point

Properties

logs from previous model

High sand proportion
No well-well shale correlation
Calcite nodules 2-4 % of GRV

Grid

High marker control
Depth conversion (top surf.)
- Error map
- U: +/-3% in GRV (200 real.)
Bounding faults U: +/-3% in GRV


chosen option

keep all except new Sw logs (n,m - Archie)
→ 3 J-functions for initialization
→ 1 kept after early HM


Facies: Sand / Shale (SIS) with VSP
K/Phi: Gaussian sim. (shale inactive)
NTG

Use most likely top surface
Isochore down
50*50*1 m³ / no upscaling

single static realisation: base case



Vertical Sand Proportion (VSP)




Identify Phase – Prove Feasibility


Manual HM (focus: South and oil prod.)

- sensible parameters: Kv/Kh, Rel perm
- need to include vertical baffle

control from SCAL data



also seen in 4D seismic



Well Concept

- volume balance in South tank
- avoid closing current producers



Liquid [Sm3/D]	Pres [Bar]	
	≈ 200	230
A-4 K	3480	4500
A-9 T3	3564	4000
A-10 AT2	3895	4250
A-16 B	3331	4150
A-34 C	3409	3900
Total Production	17679	20800
Total Injection	14500	14500
+1 producer		4250
+1 injector		10000
Total Production		25050
Total Injection		24500

Well-Pair:
1 producer
1 injector

Well Locations

- same strategy as hist. wells: 2D prob.
- limited number of tested configurations
- use 2D maps for producer

Seismic attic oil map
(4D map also)




Drilling & Well Dept.


iterations

Identify Phase – Prove Feasibility

- Reserves estimate: field delta oil production - 6 cases
 - 2 HMs
 - Different prediction settings in the “Do Nothing” case (reservoir pressure)



Well-Pair



injector close to old producer, convenient slot (well cost)

Project approved

Select Phase – Optimize


■ Part 1: still using the base case static model and the 2 HMs

Compare Well-Pair with other **concepts** (>10)

- [1-2] new wells
- use active wells for injection or short sidetracked prod.
- economic screening


Well-Pair ranks best
Producer before injector

Injector location
- tested every 250 m



Move injector
~ 500 m South

Simulation baffle tested
against synthetic 4D seismic



Baffle "confirmed"
and mapped with
3D seismic

Statfjord Revitalization

Select Phase – Uncertainty




Part 2: more static realisations

Petrophysical update (unpredicted)

- core data is now stress corrected
- K/Phi correlation clarified


- Variograms (facies, props.)
- seeds
- small range in STOIP



Workflow – “discrete” variables

- 25 static realizations..... a: [1-25]
- 3 “dynamic sets” b: [1-3]
1 → HMBC16 / 2 → intermediate / 3 → HMBC16_2
- 3 fault scenarios..... c: [1-3]

case name: **XXX_a_b_c** (all combinations)





4D baffle geometries



From previous phase:
Kv/Kh
Rel. perm

Reserves Estimate

- cases assumed a priori equiprobable
- for each case - HM mark (criteria, OF)
- screening or “weighting”




Select Phase – Posterior Analysis



Impact of input variables

Maps: posterior justification for the WP location



Project approved: wells to be drilled in 2017

Conclusion

- How is the uncertainty on the well-pair evaluation evolving during the project ?
 - confidence is building up after each milestone (decision)
 - complexity and number of parameters is increasing

- The exercise of looking back at the full project workflow is performed too rarely

Brage Statfjord Revitalization

Subsurface Workflow during an Infill Well Project



Shaping the future.

Acknowledgements to Petech colleagues and our license partners:



Questions ?